TECHNICAL PARAMETERS OF WATER HEATERS Parameters for the water heater and storage tank CTC FerroModul T 300L Model(s): No Conventional water heater: No Heat pump water heater: Solar water heater: No Yes Back-up immersion heater: No Storage tank: General data kWh Daily electricity consumption Q_{elec} NA NA % **Energy efficiency** wh Energy efficiency class Annual electricity consumption **AEC** NA kWh Declared load profile NA 15 Sound power level indoors L_{WA} dB Fossil and/or biomass fuel heated water heater kWh Daily electricity consumption Q_{fuel} NA NA Emissions of nitrogen oxides (dioxide) NO_{x} mg/kWh Solar heated water heater m^{2} Collector aperture area A_{sol} Na Zero-loss efficiency η_0 Na First-order coefficient Na $W/(m^2 K)$ a_1 Second-order coefficient Na $W/(m^2 K)$ a_2 Na Incidence angle modifier IAM Pump power consumption (solpump) Na W Na Standby power consumption (solstandby) W Heat pump heated water heater NA dB Sound power level outdoors L_{WA} Technical paremeter at declared load profile Storage water heater (3XS, XXS, XS) Volym NA Blandad vol 40° NA Storage water heater (S, M, XL, XXL, 3XL, 4XL) L VV Smart controller Weekly fuel consumption with smart NA kWh Q fuel, week, smart $Q_{\text{elec, week, smart}}$ NA kWh Weekly electricity consumption with smart NA Weekly fuel consumption without smart kWh Q fuel, week

Specific precautions and end of life information:

Weekly electricity consumption without smart

Technical parameters for storagetank

Storage volume

Standing loss

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household waste is not permitted.

kWh

280 L 96,0 W

Detailed Contact data: Enertech AB, Box 309, 341 26 Ljungby www.ctc.se 180328

Q elec, week

٧

S

NA