



Underlag borrtillstånd

bergvärmepumpar

Produkt		CTC EcoTouch 500			
Modell		520	525	534	542
Avgiven effekt B0/W35 min - max	kW	10.7 - 21.3	12.8 - 25.6	17.0 - 34.1	21.2 - 42.4
Tillförd effekt B0/W35 min - max	kW	2.2 - 4.7	2.8 - 5.6	3.8 - 7.5	4.6 - 9.2
Kyleffekt B0/W35 max	kW	16.6	20.0	26.6	33.2
Köldmedie		R410A	R410A	R410A	R410A
Köldmediemängd	kg	3.65	4.0	5.0	5.6
CO ₂ -ekvivalent	ton	7.621	8.352	10.440	11.693
Startström min - max	A	26 - 52	31 - 62	38 - 75	51 - 102

Produkt		CTC EcoTouch 500 DT		
Modell		550 DT	570 DT	585 DT
Avgiven effekt B0/W35 min - max	kW	12.8 - 51.2	17.4 - 68.3	21.2 - 84.9
Tillförd effekt B0/W35 min - max	kW	2.8 - 11.1	3.8 - 15.0	4.6 - 18.3
Kyleffekt B0/W35 max	kW	50.1	53.3	66.6
Köldmedie		R410A	R410A	R410A
Köldmediemängd	kg	2x 2.6	2x 3.4	2x 3.7
CO ₂ -ekvivalent	ton	2x 5.429	2x 7.100	2x 7.726
Startström max	A	62	75	102

Produkt		CTC EcoTouch 500 DT AD		
Modell		550 DT AD	570 DT AD	585 DT AD
Avgiven effekt B0/W35 min - max	kW	12.8 - 51.2	17.4 - 68.3	21.2 - 84.9
Tillförd effekt B0/W35 min - max	kW	2.8 - 11.1	3.8 - 15.0	4.6 - 18.3
Kyleffekt B0/W35 max	kW	50.1	53.3	66.6
Köldmedie		R410A	R410A	R410A
Köldmediemängd	kg	2x 2.6	2x 3.4	2x 3.7
CO ₂ -ekvivalent	ton	2x 5.429	2x 7.100	2x 7.726
Startström max	A	31.0	37.5	51.0





Underlag borrhåll bergvärmepumpar

Produkt		CTC EcoTouch 5000				
Modell		5048	5055	5065	5070	5085
Avgiven effekt B0/W35 min - max	kW	23.8 - 47.6	28.3 - 56.6	32.1 - 62.2	35.7 - 71.4	42.3 - 84.6
Tillförd effekt B0/W35 min - max	kW	5.2 - 10.4	6.0 - 12.0	6.8 - 13.6	7.6 - 15.2	9.2 - 18.3
Kyleffekt B0/W35 max	kW	37.2	44.6	50.6	56.2	66.3
Köldmedie		R410A	R410A	R410A	R410A	R410A
Köldmediemängd	kg	9.0	9.0	9.5	10.3	10.6
CO ₂ -ekvivalent	ton	18.792	18.792	19.836	21.506	22.133
Startström max	A	111	118	118	140	174

Produkt		CTC EcoTouch 5000 AD				
Modell		5048 AD	5055 AD	5065 AD	5070 AD	5085 AD
Avgiven effekt B0-W35 min - max	kW	23.8 - 47.6	28.3 - 56.6	32.1 - 62.2	35.7 - 71.4	42.3 - 84.6
Tillförd effekt B0-W35 min - max	kW	5.2 - 10.4	6.0 - 12.0	6.8 - 13.6	7.6 - 15.2	9.2 - 18.3
Kyleffekt B0-W35 max	kW	37.2	44.6	50.6	56.2	66.3
Köldmedie		R410A	R410A	R410A	R410A	R410A
Köldmediemängd	kg	9.0	9.0	9.5	10.3	10.6
CO ₂ -ekvivalent	ton	18.792	18.792	19.836	21.506	22.133
Startström max	A	56	59	59	70	87

Produkt		CTC EcoTouch 5100			
Modell		5110	5140	5180	5230
Avgiven effekt B0-W35 min - max	kW	55.6 - 111.1	70.2 - 140.3	90.8 - 181.5	112.4 - 224.8
Tillförd effekt B0-W35 min - max	kW	11.6 - 23.2	14.7 - 29.4	18.7 - 29.4	23.7 - 47.3
Kyleffekt B0-W35 max	kW	87,9	110,9	144,1	177,5
Köldmedie		R410A	R410A	R410A	R410A
Köldmediemängd	kg	17.5	20.7	25.5	27.0
CO ₂ -ekvivalent	ton	36.540	43.222	53.244	56.376
Startström max	A	240	287	310	408

Produkt		CTC EcoTouch 5100 AD			
Modell		5110 AD	5140 AD	5180 AD	5230 AD
Avgiven effekt B0/W35 min - max	kW	55.6 - 111.1	70.2 - 140.3	90.8 - 181.5	112.4 - 224.8
Tillförd effekt B0/W35 min - max	kW	11.6 - 23.2	14.7 - 29.4	18.7 - 29.4	23.7 - 47.3
Kyleffekt B0/W35 max	kW	87,9	110,9	144,1	177,5
Köldmedie		R410A	R410A	R410A	R410A
Köldmediemängd	kg	17.5	20.7	25.5	27.0
CO ₂ -ekvivalent	ton	36.540	43.222	53.244	56.376
Startström max	A	120,0	143.5	155.0	204.0

